


Technical drawing showing dimensions: Ø 114 (inner diameter), 25 (height), 8 (mounting tab width), and Ø 155 (outer diameter).

Thekla Lux

10 - 30 V	Gehäuse housing	Lichttemperatur Colour temperatur	9 W IP 66
QL47001	hochglanz polished	warmweiß Warm white	2900 - 3100 K

IP66, CE, F, III, Green checkmark, Recycle symbol




Technical drawing showing dimensions: Ø 185 (inner diameter), 42 (height), 5 (mounting tab width), and Ø 235 (outer diameter).

KLEOS 235

20 - 30 V	Gehäuse housing	Lichttemperatur Colour temperatur	15 W IP 66
QL48001	hochglanz polished	warmweiß Warm white	2900 - 3100 K

IP66, CE, F, III, Green checkmark, Recycle symbol




Technical drawing showing dimensions: Ø 54 (inner diameter), 16 (height), 15 (base height), and Ø 72 (outer diameter).

Bryan CS switch

10 - 30 V	Gehäuse housing	Lichttemperatur Colour temperatur	2 W IP 40
QL18001	hochglanz polished	warmweiß Warm white	2800 - 3100 K

IP40, CE, F, III, Green checkmark, Recycle symbol



Technical drawing showing dimensions: 145 (height) and Ø 64 (outer diameter).

Mirò

10 - 15 V	Gehäuse housing	Lichttemperatur Colour temperatur	2 W IP 40
QL09001	hochglanz polished	warmweiß Warm white	2800 - 3100 K
QL09002	weiß white	warmweiß Warm white	2800 - 3100 K

IP40, CE, F, III, Green checkmark, Recycle symbol



Technical drawing showing dimensions: 140 (width), 116 (height), and 13 (thickness).

**126 Hochleistungs LED
126 High luminosity LED**

Action

9 - 16 V	Gehäuse housing	Lichttemperatur Colour temperatur	5 W IP 66
QL3500106605	weiß white	DayLight	3800 - 4100 K

IP66, CE, F, III, Green checkmark, Recycle symbol